

# SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

## Fiddes Liquid Floor Wax.

Revision 0

Revision date 2015-06-01

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** Fiddes Liquid Floor Wax.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Description** No data is available on this product.

#### 1.3. Details of the supplier of the safety data sheet

**Company** Fiddes & Son Ltd  
**Address** Florence Works, Brindley Road, Cardiff, South Glamorgan, CF11 8TX  
**Web** www.fiddes.co.uk  
**Telephone** +44 (0)29 2034 0323  
**Fax** +44 (0)29 2034 3235  
**Email** info@fiddes.co.uk  
**Email address of the competent person** info@fiddes.co.uk

#### 1.4. Emergency telephone number

**Emergency telephone number** 1-352-323-3500  
**Company** INFOTRAC  
24HR

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**2.1.1. Classification - 67/548/EEC** Xn; R65 N; R51/53 R10-66-67  
Symbols: Xn: Harmful. N: Dangerous for the environment.

**Main hazards** Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

**2.1.2. Classification - EC 1272/2008** EUH066; Flam. Liq. 3: H226; STOT SE 3: H336; Aquatic Chronic 2: H411;

#### 2.2. Label elements

##### Hazard pictograms



##### Signal Word

Warning

##### Hazard Statement

EUH066 - Repeated exposure may cause skin dryness or cracking.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
STOT SE 3: H336 - May cause drowsiness or dizziness.  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

##### Precautionary Statement: Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Fiddes Liquid Floor Wax.

Revision 0

Revision date 2015-06-01

## 2.2. Label elements

<b>Precautionary Statement: Response</b>	P233 - Keep container tightly closed. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P370+P378 - In case of fire: Use foam/C02 to extinguish.
<b>Precautionary Statement: Storage</b>	P102 - Keep out of reach of children. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up.
<b>Precautionary Statement: Disposal</b>	Dispose of this material and its container to hazardous or special waste collection point.

## SECTION 3: Composition/information on ingredients

## 3.1. Substances

## 67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Hydrocarbons C7-C9, n-alkanes, isoalkanes, cylics		64742-49-0	920-750-0	01-2119473851-33	40 - 50%	F; R11 Xn; R65 N; R51/53 R66-67	

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Hydrocarbons C7-C9, n-alkanes, isoalkanes, cylics		64742-49-0	920-750-0	01-2119473851-33	40 - 50%	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411;	

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

<b>Inhalation</b>	Remove casualty from exposure ensuring one's own safety whilst doing so.
<b>Eye contact</b>	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
<b>Skin contact</b>	Remove contaminated clothing. Wash off immediately with plenty of soap and water.
<b>Ingestion</b>	DO NOT INDUCE VOMITING.

## 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation</b>	Harmful by inhalation.
<b>Eye contact</b>	Harmful.
<b>Skin contact</b>	Harmful in contact with skin.
<b>Ingestion</b>	Harmful if swallowed.

## 4.3. Indication of any immediate medical attention and special treatment needed

<b>Inhalation</b>	Seek medical attention.
<b>Eye contact</b>	Seek medical attention.
<b>Skin contact</b>	Seek medical attention.
<b>Ingestion</b>	Seek medical attention.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions. Vapour may travel considerable distance to source of ignition and flash back.
--	---

## 5.2. Special hazards arising from the substance or mixture

# Fiddes Liquid Floor Wax.

Revision 0

Revision date 2015-06-01

## 5.2. Special hazards arising from the substance or mixture

Flammable liquid. Burning produces irritating, toxic and obnoxious fumes.

## 5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Keep public away from danger area. Keep upwind.

### 6.2. Environmental precautions

Avoid release to the environment. Refer to special instructions/Safety data sheets. Do not allow product to enter drains.

### 6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal.

### 6.4. Reference to other sections

See section 2, 3, 8, 13 for further information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Adopt best Manual Handling considerations when handling, carrying and dispensing.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed in a cool place. Store at temperatures between 5 °C and 18 °C.

### 7.3. Specific end use(s)


No data is available on this product.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

See section 8.2 for further information.

### 8.2. Exposure controls



#### 8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

#### Eye / face protection

Wear eye/face protection.

#### Skin protection - Handprotection

Chemical resistant gloves (PVC).

#### Skin protection - Other

Wear suitable protective clothing.

#### Respiratory protection

Wear suitable respiratory equipment when necessary.

#### 8.2.3. Environmental exposure controls

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

## Fiddes Liquid Floor Wax.

Revision 0

Revision date 2015-06-01

## 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	White
Odour	Characteristic
pH	No data available
Melting point	No data available
Initial boiling point	No data available
Flash point	23 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Relative density	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Solubility	Immiscible in water

## 9.2. Other information

Conductivity	No data available
Surface tension	No data available
Benzene Content	No data available
Lead content	No data available
VOC (Volatile organic compounds)	642 g/l

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

	No data available.
--	--------------------

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## 10.3. Possibility of hazardous reactions

	No data is available on this product.
--	---------------------------------------

## 10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

## 10.5. Incompatible materials

	Oxidising agents.
--	-------------------

## 10.6. Hazardous decomposition products

	Burning produces irritating, toxic and obnoxious fumes.
--	---

## SECTION 11: Toxicological information

## 11.1.4. Toxicological Information

Hydrocarbons C7-C9, n-alkanes, isoalkanes, cylics	Inhalation Rat LC50/4 h: 23300	Oral Rat LD50: 5840
---	--------------------------------	---------------------

## SECTION 12: Ecological information

## 12.1. Toxicity

Hydrocarbons C7-C9, n-alkanes, isoalkanes, cylics	Daphnia EC50/48h: 4.600000 mg/l	Fish LC50/96h: 3.000000 mg/l
---	---------------------------------	------------------------------

## 12.2. Persistence and degradability

## Fiddes Liquid Floor Wax.

Revision 0

Revision date 2015-06-01

## 12.2. Persistence and degradability

No data is available on this product.

## 12.3. Bioaccumulative potential

No data is available on this product.

## Partition coefficient

Fiddes Liquid Floor Wax. No data available	Hydrocarbons C7-C9, n-alkanes, isoalkanes, cylics No data available
--	---

## 12.4. Mobility in soil

No data is available on this product.

## 12.5. Results of PBT and vPvB assessment

No data is available on this product.

## 12.6. Other adverse effects

No data is available on this product.

## SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

Dispose of as special waste in compliance with local and national regulations.

## SECTION 14: Transport information

## Hazard pictograms



## 14.1. UN number

UN1263

## 14.2. UN proper shipping name

PAINT RELATED MATERIAL

## 14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

## 14.4. Packing group

Packing group II

## 14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

## ADR/RID

Hazard ID	33
Tunnel Category	(D/E)

## IMDG

EmS Code F-E S-E

## Fiddes Liquid Floor Wax.

Revision 0

Revision date 2015-06-01

IATA	
Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	353
Maximum quantity	5 L
SECTION 15: Regulatory information	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
Regulations	<p>COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p> <p>REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p>
15.2. Chemical safety assessment	
	No data is available on this product.
SECTION 16: Other information	
Other information	
Text of risk phrases in Section 3	<p>R11 - Highly flammable.</p> <p>R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R65 - Harmful: may cause lung damage if swallowed.</p> <p>R66 - Repeated exposure may cause skin dryness or cracking.</p> <p>R67 - Vapours may cause drowsiness and dizziness.</p>
Text of Hazard Statements in Section 3	<p>Flam. Liq. 2: H225 - Highly flammable liquid and vapour.</p> <p>Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.</p> <p>Skin Irrit. 2: H315 - Causes skin irritation.</p> <p>STOT SE 3: H336 - May cause drowsiness or dizziness.</p> <p>Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.</p>
Maximum content of VOC	642 g/l.
General information	
	This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy.